Ultrabond Urethane Cleaner

Professional Adhesive Remover





DESCRIPTION

Ultrabond® Urethane Cleaner is a ready-to-use urethane adhesive cleaner designed to effectively remove wet urethane adhesive residues, such as *Ultrabond ECO® 975*, *Ultrabond ECO 980* and *Ultrabond ECO 995*, from the surface of prefinished wood flooring. It is low-odor, nonflammable, pH-neutral and biodegradable. Safe for use on most types of prefinished wood flooring including parquet, engineered, solid and bamboo, *Ultrabond Urethane Cleaner* also removes urethane adhesive from trowels and tools.

FEATURES AND BENEFITS

- Removes wet urethane adhesives from wood-flooring surface
- Won't leave a residue on the surface
- Cleans tools and is nonflammable

WHERE TO USE

- Interior residential wood-flooring installations
- Interior commercial wood-flooring installations

LIMITATIONS

- Do not use as a hand-cleaner. Use gloves to protect skin.
- Protect carpeting, wood cabinets, painted surfaces and other finished surfaces.

- Avoid spilling excess amounts of *Ultrabond Urethane Cleaner*, which may seep in between wood flooring and weaken the bond of the urethane adhesive. Keep an absorbent product handy (paper towels, sawdust, kitty litter, etc.) to absorb spills.
- Do not leave *Ultrabond Urethane Cleaner* on the surface of the wood flooring for longer than 60 minutes.
- Thoroughly rinse and dry the area of application after use.

MIXING

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

- Ready to use; no mixing is necessary

PRODUCT APPLICATION

Urethane adhesives are very difficult to remove once dry and cured. During the installation of glue-down wood flooring, make every effort to prevent adhesive from getting on the flooring surface. For best results, remove adhesive smudges and drops immediately during installation.

Read all installation instructions thoroughly before installation.

Test for compatibility with flooring in a small inconspicuous area before using.

Avoid using metal blades or other sharp objects when removing the adhesive, as this can permanently damage the surface of the finished floor.

For removing fresh, wet urethane adhesives or membranes from prefinished wood flooring during the installation of glue-down wood flooring:

1. Dampen a nonabrasive, clean white towel or cloth with *Ultrabond Urethane Cleaner*.
2. Place the towel/cloth on fresh, wet adhesive and allow to remain for about 5 to 10 minutes.
3. Remove adhesive with the soft, clean white towel.
4. Rinse the area completely with clean soapy water.
5. Dry the area with another soft, clean white towel.

For removing semi-dry urethane adhesives or membranes from prefinished wood flooring after the installation is complete (up to 6 hours after installation):

1. Place a soft, clean white towel soaked with *Ultrabond Urethane Cleaner*.
2. Allow the cleaner to remain on the dried adhesive for about 30 minutes.
3. Gently scrape the softened adhesive, using a plastic tool such as an automotive ice scraper or putty knife. Do not use metal blades or scrapers.
4. Remove loose adhesive with the soft, clean white towel.
5. Rinse the area completely with clean soapy water.
6. Dry the area with another soft, clean white towel.
7. Repeat if necessary.

For removing urethane residues from trowels and tools:

1. Soak trowels and tools in *Ultrabond Urethane Cleaner*.
2. Scrape and/or wipe off softened adhesive.
3. Rinse tools with clean soapy water and allow to dry.

Product Performance Properties

Laboratory Tests	Results
VOCs (Rule #1168 of California's SCAQMD)	< 575 g per L
Odor	Slightly sweet
Density	8.2 to 8.3 lbs. per U.S. gal. (0.9 to 1.0 g per mL)
Consistency	Liquid
Color	Clear
Shelf life	2 years when stored in original packaging at 73°F (23°C)
Storage conditions	50°F to 90°F (10°C to 32°C)
Flash point (Tag)	> 200°F (93°C)

Protect containers from freezing in transit and storage. Provide for heated storage on site and deliver all materials at least 24 hours before work begins.

Packaging

Size
Jug: 1 U.S. qt. (946 mL)

ADDITIONAL INFORMATION

Refer to the Safety Data Sheet (SDS) for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability-durabilite@mapei.com.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**
Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America
1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services
U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service
1-800-42-MAPEI (1-800-426-2734)

Edition Date: June 6, 2023 MK 3000001 (23-1053)

For the most current product data and BEST-BACKED[SM] warranty information, visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.